

mini-Ligno DX Moisture Meter

Description:

The mini-Ligno DX is a pin meter calibrated to measure wood, panel products, bamboo, gypsum, drywall and other building materials. The mini-Ligno DX is used in flooring, woodworking, cabinet making as well as construction, restoration and home inspection. Veneer mills use the meter for its sensitivity to surface moisture and thin materials.

Advanced Multi-Purpose Moisture Meter: The DX includes 42 different calibrations for testing a variety of wood species, panel products, subfloors and bamboo. A great meter for the hardwood floor installer who comes across many different species of wood and bamboo. We continuously add new species and engineered products to the wood group list to give you an up-to-date meter.

For restoration, construction and home inspection: The measuring range is wide enough to measure dry and wet materials to pinpoint problem areas in the building envelope. Drywall scales and reference scale for non-wood building materials allow easy identification of different moisture levels.

If the pins on the meter (7/16", 10mm) cannot reach deep enough, select the mini-Ligno DX/C and add electrode E12 to measure thicker wood, electrode E14-m to reach deeper to check roofs, walls or floors and in-kiln cables for a dry kiln.

Features:

- Wide measuring range for wood 5-65% (dependent on wood species)
 - Multiple corrections built-in for domestic and tropical wood species, sub floors, panel products, drywall and other building materials
 - Display: Shock-proof, high-emitting, bright LED, easy to read in poorly lit areas
 - Resolution: 0.1% up to 10%, reads 1% steps above 10%. Lifetime warranty.
 - Ergonomic design for easy operation, durable and rugged, built to last
 - Automatic shut off
 - Temperature stable circuitry with built-in automatic calibration check
- The mini-Ligno DX has a 2-year warranty, display has a lifetime warranty, accessories have a 1-year warranty, pins and battery are excluded.

Specifications:

Size: 5.5"L X 2.75"W X 1"H

Measuring Range: Wood: 5-65%

Gypsum, Sheetrock, Wall Boards: 0-7.5%

Reference Scale: 0-99

Display: Resolution: 0.1% below 10% and 1% steps above 10%, life-time warranty
Calibrated for a wood temp of 70°F (20°C).

A correction table for different wood temperatures is listed in the manual.

Species Corrections:

42 settings to correct for:

- domestic and tropical wood species, subfloors, OSB, AdvanTech
- wood-based panel products, laminates
- bamboos, vertical, horizontal and strand

3 Scales for gypsum, drywall, exterior and interior wall boards (%)

1 Reference Scale for building materials, concrete, tile...,

for identification of moisture levels in Search and Compare Mode.

Includes:

- 1 mini-Ligno DX meter with wrist strap in carrying pouch with belt loop, 1 9V battery
- 1 laminated wood group card and 1 instruction manual
- 2 pair pins: 1 pair of 3/16" and 1 pair of 7/16" measuring depth (5mm, 10mm)

Specifications are subject to change without notice.



Quality, performance and price have made mini-Lignos one of our most popular moisture meters.



Easy to use and accurate, multiple wood species corrections. Ideal for woodworking, furniture and cabinet manufacturing.



Smart design – built tough.
Green cap serves as handle for easy pin insertion and covers pins for safe transportation. Strap keeps meter in reach.



Lignomat USA LTD, 14345 NE Morris Ct., Portland OR 97230,
503-257-8957, 800-227-2105, sales@lignomat.com www.lignomat.com