

### Check / Change Wood Group Settings for MD and MD/C

(For complete manual see User Instructions 2.1 and 1.1)

Wait until mini-Ligno is off, then double click on-off switch between pins fast. Red number (2 or 3) indicates active setting. Click again to change setting. If the wood species is known use yellow species card to find correct setting. If you do not know the wood species or if you want to measure other materials use the settings listed below. **If possible, measure dry material for comparison**

Lignomat USA Ltd.  
14345 NE Morris Ct.  
Portland OR, 97230 USA  
www.lignomat.com  
e-mail: sales@lignomat.com  
Tel: 800-227-2105  
503-257-8957

	Framing Lumber	Particle Board Plywood Moldings	OSB	Hardwood Floors	Sheet-rock	Reference scale for other materials
<b>Settings for MD, MD/C</b>	<b>3</b>	<b>3</b>	<b>2</b>	<b>2</b>	<b>2</b>	<b>2</b>
Suggested Moisture Range**	below 19%	9-12%	9-12%	6-9%	6-11	WME Scale
Permissible Moisture Range**	can vary by job, season, location.					

### Settings for mini-Ligno MD, MDC

#### Woodgroup 2

Abachi  
Acacia  
Afrosmosia  
Bamboo  
Beech  
Cedar (all types)  
Cumaru  
Dogwood  
Gonzales Alves  
Iroko  
Jatoba  
Koa  
Locust  
Oak Red / White  
Poplar  
Ramin  
Rosewood  
Teak  
Wenge  
Zebra Wood  
Hardbaord  
OSB

#### Woodgroup 3

Alder  
Ash  
Aspen  
Balsa  
Basswood  
Birch  
Cherry  
Cottonwood  
Cypress  
Elm  
Fir Douglas  
Gum  
Hemlock  
Kempas  
Larch  
Lauan (white / red)  
Mahogany  
Maple  
Meranti (dark / red)  
Merbau  
Myrtlewood  
Oak European  
Pine  
Pine Southern Yellow  
Redwood  
Spruce  
Tigerwood  
Walnut  
Particleboard